


VOLA T60, T65, T68

Fitting instruction
Montageanleitung
Monteringsvejledning
Monteringsvægledning
Montage hanleiding
Manuel de montage



www.vola.com

T60-T65-T68_V3_40998980
23-08-2023



1 T60

Data	Bar:	1	2	3	4	5
T60	(l/min)	6.9	9.8	12	14	15
	(Gal/min)	1.8	2.6	3.2	3.7	4.1

Max. 65°C. 150°F

Service - VR556

USA: Max. flow rate: 1.6 Gal/min 6.0 l/min.

Bathtub
Badewanne

Badekar
Badkar

Badkuip
Baignoire



2 T68

T8 → T68



3 T65

Height	790 mm	690 mm	590 mm	490 mm
31"	27 1/8"	23 1/8"	19 1/4"	
Height	900 mm	800 mm	700 mm	600 mm
35 3/8"	31 1/2"	27 1/2"	23 5/8"	

4

490 mm
19 1/4"590 mm
23 1/4"690 mm
27 1/8"790 mm
31"


5

Ø6 mm
Ø15/64"24 - 42 mm
1" - 1 3/4"Ø54 mm
Ø2 1/8"



4 mm

61 mm
2 3/8"54 mm
2 1/8"

6



4 mm

490 mm
19 1/4"590 mm
23 1/4"690 mm
27 1/8"790 mm
31"

Alt.:

180°


7



8

2 mm





vola
 Lunavej 2
 DK-8700 Horsens
 Tlf : + 45 7023 5500
 Fax: + 45 7023 5511
 sales@vola.com
 www.vola.com

VOLA T68

Date
 Mar. 15

Rev.
 0

Sheet
SB 42.68